

Page 1 of 6 MSDS-E-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 3.0

			1. PRO	DUCT IDEN	ITIFICATION			
1.1	Product Name: DeoxIT® D-Series, 5% Spray, (P/N D5S-6), 142 g							
1.2	Chemical Name: See ingredients listed in section 3							
1.3	Synonyms: DeoxIT®, D5S-6, 5% Spray							
1.4	Trade Names: DeoxIT®, D5S-6, 5% Spray							
1.5	Product Use: Clean, deoxidize & improve electrical contacts & connectors							
1.6	Manufacturer's Name: CAIG Laboratories, Inc.							
1.7	Manufacturer's Address: 12200 Thatcher Court, Poway, CA 92064-6876 USA							
1.8	Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-3887							
1.9	Business Phone: +1 (800)-224-4123							
1.10	Other Product Names:	DeoxIT [®] , D5MS-15,	5% Spray, 14 g					
			2. HAZ	ARD IDEN	TIFICATION			
	This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008(2004) and ADG Code (Australia). WARNING! Flammable aerosol. Colorless, volatile liquid with ethereal and faint sweetish odor. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. Hazard Statements (H): H223 – Flammable aerosol. Precautionary Statements (P): P210 – Keep away from heat/sparks/open flames/hot surfaces. P211 – Do not spray on an open flame or other ignition source. P251 – Pressurized container. Do not pierce or burn, even after use. P280 – Wear protective gloves and eyewear. P302 + P352 – IF ON SKIN – Wash with plenty of soap and water. P312 – Call a Poison Control Center or doctor/physician if you feel unwell. P333 + P313 – If skin irritation or rash occurs, get medical advise/attention. P321 – Refer to section 4 of this Safety Data Sheet (First Aid). P305+P351+P338 – IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P501 – Dispose of contents/container through licensed treatment, storage or disposal facility.							
2.2	Routes of Entry:		Inhalation:	YES	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure: EYES: SKIN: INGESTION: INHALATION:	rash). Gastrointestinal irrita	l skin sensitizer. Pro	ervous system	-		ntact dermatitis ((localized redness or
2.4	Symptoms of Overexposure	Mild irritation, redne						
	SKIN: Contact dermatitis, characterized by localized red or puffy dry skin and itching. INGESTION: Nausea, vomiting, and diarrhea.							
0.5	INHALATION:	Mouth, nose, and the	roat irritation, dizzin	ess, nausea,	light-headedness, d	runkennes	s, and loss of coc	ordination.
2.5	Acute Health Effects: INGESTION: Gastrointestinal irritation and central nervous system depression. EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (e.g., localiz redness and/or rash).					atitis (e.g., localized		
	INGESTION: INHALATION:	Gastrointestinal irrita Central nervous syst		•	n depression. upper respiratory tra	ct.		
2.6	Chronic Health Effects: EYES: SKIN:	Mild to moderate irri Irritant and potentic redness and/or rash	itation. 11 skin sensitizer.).	Prolonged o	r repeated contact		e contact derm	atitis (e.g., localized
	INGESTION: INHALATION:	Gastrointestinal irrita Central nervous syst			n depression. upper respiratory tra	ct.		
2.7	Target Organs: Eyes, skin and resp	iratory system.						
		D = Not Determined; N red information is inclu		-				



Page 2 of 6 **MSDS-E-D5S-A**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 3.0

		3.	COMPOSIT	ION & ING	REDIEN	T INFO	DRM/	ATION	1					
								EX	POSUR	E LIMITS	IN AIR	(mg/m ³)	
						ACO	GIH		NOHSC			OSHA		
						pp	m		ppm			ppm		OTHER
	CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- Stel	ES- PEAK	PEL	STEL	IDLH	
PETRO	DLEUM NAPHTHA	64742-88-7	X\$5250000	265-191-7	40-70	100	NE	100	NE	NE	NA	NE	NE	
DIFLU	OROETHANE (R-152a)	75-37-6	KI4100000	200-866-1	10-30	1000	NA	1000	NA	NA	NE	NA	NA	SKIN
Deox	IT® D-Series, D100L	TRADE SECRE	T		3-7	NA	NA	NA	NA	NA	15	NA	NA	
4.1	First Aid:		4.	. FIRST AID	MEASU	JKE2								
4.1	EYES: Flush e flushing	yes thoroughly g. If irritation po	ersists, seek in	nmediate med	dical atte	ntion.								-
		e contaminate al attention. De	-									i persi:	sis, se	ek prompr
	INGESTION: Drink p	lenty of water.	If irritation pe	ersists, contact	t a physic	ian.								
		e victim to fre al attention. If						ster su	pplem	ental (oxyge	n and	seek	immediate
4.2	Medical Conditions Aggravated by Expo None reported by the ma							HEAL	.TH					1
	None reponed by me ma	inoraciorei.						FLAN	MAE	BILITY				2
								PHYS		HAZ	ARDS			0
								PROT	ECTI	VE EG	QUIPA	NENT		В
								EYES		SKIN				
			5. F	IREFIGHTIN	IG MEA	SURE	S							
5.1	Flashpoint & Method: 48.8 °C - 54.4 °C (120 °F -	130 °F).												
5.2														
5.3	Flammability Limits:		Lower Explos	ive Limit (LEL):		NA		Upper I	Explosiv	e Limit	(UEL):		N	A
5.4	Fire & Explosion Hazards:					-								
	Level 2 aerosol. Carbon o	dioxide, carbo	n monoxide, l	hydrocarbons	•									
5.5	Extinguishing Methods: CO ₂ , Alcohol foam, Dry Chen	nical, Water Fog												
5.6	Firefighting Procedures:													
	Wear NIOSH/MSHA approved self-contained breathing apparatus and protective clothing. Use a water spray to cool containers involved in fire. Do not use direct water stream. Container storage areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Keep containers cool until well after the fire is out to prevent rupture. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.													
ļ,			6. ACC	IDENTAL RE	LEASE	MEAS	URES							
6.1	Spills: Secure spill area and de protective equipment. A commercial absorbent m of the spill to prevent run and/or reporting requirem	area may beco naterial. Place noff into sewer	ome slippery. into leak-pro	Absorb prod of, U.S. DOT-aj	luct onto pproved	porou: contair	s mate ners. If	erial, su neces	uch as sary, (sand, cover c	clay, all drai	diaton ns and	naceo dike	us earth or well ahead



Page 3 of 6 **MSDS-E-D5S-A**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 3.0

		7. HANDLING & STORAGE INFORMATION						
7.1	Work & Hygiene Practices: Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact.							
7.2	Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Normal shelf-life: 2-3 years.							
7.3								
8.1	Ventilation & Engineering Controls:	8. EXPOSURE CONTROLS & PERSONAL PROTECTION						
	Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).							
8.2	Respiratory Protection: None required, when used w	ith adequate ventilation.						
8.3		shields (ANSI Z87) under normal use conditions.						
8.4	Hand Protection: None required under norma rubber or impervious plastic	Il conditions of use. However, may cause skin irritation in some sensitive individuals. In such cases, wear gloves.						
8.5	Body Protection: Use as necessary to prevent	skin contact						
	use as necessary to prevent	Skir Condei.						
		9. PHYSICAL & CHEMICAL PROPERTIES						
9.1	Density:	0.75						
9.2	Boiling Point:	171.1 °C – 204 °C @ 760 mmHg						
9.3	Melting Point:	ΝΑ						
9.4	Evaporation Rate:	0.11 (n-Butyl Acetate = 1.0)						
9.5	Vapor Pressure:	35 psig @ 20 °C, 50 psig @ 50 °C						
9.6	Molecular Weight:	ΝΑ						
9.7	Appearance & Color:	Light red, aerosol						
9.8	Odor Threshold:	Ethereal/hydrocarbon odor						
9.9	Solubility:	Not soluble in water						
9.10	рН	ND						
9.11	Viscosity:	10.0 cps						
9.12	VOC (grams/liters)	588 g/l						
9.13	Other Information:	Vapor Density = 4.9 (air = 1.0)						
		10. STABILITY & REACTIVITY						
10.1	Stability: Stable under normal condition	ons of use (see section 7)						
10.2	Hazardous Decomposition Products:							
	Change in color signifies exp	posure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.						
10.3	Hazardous Polymerization:							
	Will not occur.							
10.4	Conditions to Avoid: Use or storage near open fla trafficked areas.	mes, sparks, high heat (>100 $^\circ$ F) or other heat sources, and proximity to incompatible substances and heavily						
10.5	Incompatible Substances: Strong oxidizers.							



Page 4 of 6 MSDS-E-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 3.0

	11. TOXICOLOGICAL INFORMATION							
11.1		this						
11.2	Acute Toxicity: See section 3.5							
11.3	Chronic Taxicity: See section 3.6							
11.4	Suspected Carcinogen:							
11.5	NE This medicatic net repeated to produce reproductive toxicity in humans							
	This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans.							
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.							
	Teratogenicity: This product is not reported to produce teratogenic effects in humans.							
	Reproductive Toxicity: This product is not reported to produce reproductive effects in humans.							
11.6	Irritancy of Product: See Section 2.3							
11.7	Biological Exposure Indices:							
11.8	Physician Recommendations:							
	Treat symptomatically.							
	12. ECOLOGICAL INFORMATION							
12.1	Environmental Stability:							
12.2	This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Effects on Plants & Animals:							
12.3	There is no specific data available for this product. Effects on Aquatic Life:							
12.3	Releases of large volumes of this product are expected to be harmful or fatal to overexposed aquatic life.							
12.4	Environmental Impact (Percent by Weight): CFC: 0.0%							
	HCFC: 0.0%							
	HFC: 20.0%							
	Chlorinated Solvent: 0.0%							
	VOC: 75.0%							
	ODP: 0.0%							
	13. DISPOSAL CONSIDERATIONS							
13.1	Dispose of in accordance with federal, state or local regulations.							
13.2	Special Considerations: EPA Waste Code: D001 (characteristic - ignitability)							
	14. TRANSPORTATION INFORMATION							
	e basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Addition scriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.	onal						
14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (until 12/31/2013) UN1950, AEROSOLS, 2.1, LTD QTY (IP VOL ≤ 1.0 L)							
14.2	L IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 500 ml) UN1950, AEROSOLS, 2.1 (> 500 ml)							
14.3								
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)							
14.5	ADR/RID (EU): UN1950, AEROSOLS, 2.1, LTD QTY (IP VOL ≤ 1.0 L)							
14.6	SCT (Mexico): UN1950, AEROSOLES, 2.1, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L)	1						
14.7	ADGR (Australia): UN1950, AEROSOLS, 2.1, LTD QTY (IP VOL ≤ 1.0 L)							



Page 5 of 6 **MSDS-E-D5S-A**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 3.0

	15. REGULATORY INFORMATION						
15.1	5.1 SARA Reporting Requirements: NA						
15.2	5.2 SARA Threshold Planning Quantity: NA						
15.3							
15.4							
15.5	5.5 Other Federal Requirements:						
10.0	NA NA						
15.6	Other Canadian Regulations This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.						
15.7	State Regulatory Information: The primary component of this product is not listed on the following state lists: California OSHA; California Proposition 65; Massachusetts Right to Know List of Chemicals; New Jersey Right to Know List 8:59 Appendix A; Pennsylvania Hazardous Substances List 34 323 Appendix A; Wisconsin Hazardous Substances List NR 605.09; Minnesota Hazardous Substances List; and Florida Toxic Substances List.						
	 ^{5.8} ^{67/548/EEC: (European Union) Requirements:} The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: <u>Petroleum Naphtha</u>: Flammable, Harmful (F, Xn). <u>Risk Phrases</u> (R): 10-65 – Flammable. Harmful: may cause lung damage if swallowed. <u>Safety Phrases</u> (S): 2-23-24-62 – Keep away from children. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this MSDS or the container label. WARNING! Flammable aerosol. Colorless, volatile liquid with ethereal and faint sweetish odor. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. <u>Hazard Statements</u> (H): H223 – Flammable aerosol. <u>Precautionary Statements</u> (P): P210 – Keep away from heat/sparks/open flames/hot surfaces. P211 – Do not spray on an open flame or other ignition source. P251 – Pressurzed container. Do not pierce or burn, even affer use. P280 – Wear protective gloves and eyewear. P302 + P352 – IF ON SKIN – Wash with plenty of soap and water. P312 – Call a Poison Control Center or doctor/physician if you feel unwell. P333 + P313 – If skin irritation or rash occurs, get medical advise/attention. P321 – Refer to section 4 of this Safety Data Sheet (First Aid). P305+P351+P338 – IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P501 – Dispose of contents/container through licensed treatment, storage or disposal facility. 						
	16. OTHER INFORMATION						
16.1	16.1 Other Information:						
16.2	6.2 Terms & Definitions:						
	See last page of this MSDS.						
16.3	This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other explications must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s known information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be chatter to time. Be sure to consult the latest edition.	wledge, the guaranteed the specific					
16.4	6.4 Prepared for: CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/						
16.5	 Prepared by: ShipMate, Inc. P.O. Box 787 780 Buckaroo Trail Suite D Sisters, OR 97759 Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com 						



Page 6 of 6 MSDS-E-D5S-A

MSDS Revision Date: 08/22/2012

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number	
EXPOSURE LIM	ITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists			
TLV	TLV Threshold Limit Value			
OSHA U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit			
IDLH	Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped				
	receives manual chest compressions and breathing to circulate blood and provide			
	oxygen to the body.			


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMM
2	Moderate Hazard	PHYSIC
3	Severe Hazard	PERSON
4	Extreme Hazard	

FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:



Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of required product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:				
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ianition			
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			

HAZARD RATINGS:

MSDS Revision: 3.0

0	Minimal Hazard						
1	Slight Hazard						
2	Moderate Hazard						
3	Severe Hazard						
4	Extreme Hazard						
ACD	Acidic Alkaline						
ALK							
COR	Corrosive						
₩	Use No Water						
ОХ	Oxidizer						
TREFOIL	Radioactive						



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s				
LC 50	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD _{io}	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC _o , LC _{io} , & LC _o					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kew or log Kee	Coefficient of Oil/Water Distribution				

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System						
DOT	U.S. Department of Transportation						
TC	Transport Canada						
EPA	U.S. Environmental Protection Agency						
DSL	DSL Canadian Domestic Substance List						
NDSL	NDSL Canadian Non-Domestic Substance List						
PSL	PSL Canadian Priority Substances List						
TSCA	U.S. Toxic Substance Control Act						
EU	EU European Union (European Union Directive 67/548/EEC)						
WGK	Wassergefährdungsklassen (German Water Hazard Class)						

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

\oslash	۲	۲		1	X		
Α	В	С	D1	D2	D3	E	F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		*	¥	*		×	×
с	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		٨	\Diamond					E
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

#